

SINGLE-PIPE MANUAL VALVES

119SX

Nickel-plated 4-way valve for one-pipe systems. Connection for copper or plastic pipe. Straight tailpiece complete with flow separation probe. Flow rate to radiator : 100%. ABS handwheel.



Type	Part no.	Size	Size Tube	Kvs
119SX	119S1212X	1/2"	1/2"	1,6
119SX	119S3412X	3/4"	1/2"	2
119SX	119SS1212SX	1/2"	1/2"S	1,6
119SX	119SS3412SX	3/4"	1/2"S	2

THERMOSTATIC ACTUATORS

148



Thermostatic actuator with oil-filled sensitive element. Temperature limiting and locking device. ABS handwheel. Graduated scale from 0 to 5. Setting range : 0°C - 28°C. Anti-freeze position : 8°C. Max. differential pressure: 1.5 bar. **CEN approved EN 215 compliant.**

Type	Part no. WII	Part no. WID
148	148	-
SE148*	-	1210001

* for TVE, TVD, TVE-S and TVE-SC series.


147



Thermostatic actuator chrome-plated version with oil-filled sensitive element. Other characteristics as per Item 148

Type	Part no.
147	147CR

148SD



Thermostatic actuator with remote sensor. 2 m capillary tube. Other characteristics as per Item 148.

Type	Part no. WII	Part no. WID
148SD	148SD	1210002

148GA

Tamper-proof cover for thermostatic actuators series 148. Provision for limiting and locking temperature range on rivetable closing position. Complete with standard mounting screws and break-stem rivets.



Type	Part no. WII	Part no. WID
148GA	148GA	-
SE148GA	148GAWM	1210004