

FAN-COIL VALVES

68

C

2131

Two-way brass valve for fan-coils.

ON/OFF operation with actuators series 22C.

Max. operating temperature: 100°C. Disc stroke: 2.5 mm. Nominal pressure: 16 bar.

Type	Part no.	Size	Kvs
2131	213112	1/2" MM	1,7
2131	213134	3/4" MM	2,8
2131	21311	1" MM	4,5

3131

Three-way brass valve for fan-coils. ON/OFF operation with actuators series 22C.

Max. operating temperature: 100°C. Disc stroke: 2.5 mm. Can be used both as mixing and diverting valve, except for version 31311 which can only be used as diverting valve.

Nominal pressure: 16 bar.

The Kvs and by-pass Kvs values given in the table alongside refer to the valve used for diverting service.

Type	Part no.	Size	Kvs	Kvs By-pass
3131	313112	1/2" MM	1,7	1,3
3131	313134	3/4" MM	2,8	1,8
3131	31311	1" MM	4,5	3,1

VU

Tee fitting for creating by-pass in valves series 3131 (Dn 1").

Type	Part no.	Size
VU	VU311	1" MM

4131

Three-way brass valve with 4 connections for fan-coils. ON/OFF operation with actuators series 22C. Max. operating temperature: 100°C. Disc stroke: 2.5 mm.

Can be used both as mixing and diverting valve. Nominal pressure: 16 bar.

The Kvs and by-pass Kvs values given in the table alongside refer to the valve used for diverting service.

Type	Part no.	Size	Kvs	Kvs By-pass
4131	413112	1/2" MM	1,7	1,3
4131	413134	3/4" MM	2,8	1,8